

Description

for spot cooling.

Fan Tray 300, 600 and 900 CFM



• Rack mount fan trays provide a

cooling in electronic cabinets.

Fan travs can be positioned at the

exhaust air out of the cabinet or

bottom of an enclosure to force air through the cabinet, at the top to

below specific pieces of equipment

compact, economical solution for



Standards

· cURus recognized.

Features


- 300, 600 and 900 CFM sizes.
- 115VAC, 50/60Hz.
- 19" panel width mounting.
- Low profile 1.75" (1U) height.
- 600 and 900 CFM units include removable rear support brackets.
- Circuit breaker protected.
- 6 foot 14/3 SJTW cord with molded 3 prong plug.
- Thermally protected, ball bearing
- · Integral finger guards above and below fans.
- Shipped fully assembled.
- Available with or without ON/OFF switch.

Finish

- · Stocked in textured, black body
- Textured black face panel.

Options

- Contact Hammond for information
 - 24" panel width mounting.
 - 230 V version (with IEC 320-C14 INLET).
 - 15 foot cord
 - · Optional colors





CIRCUIT J BREAKER 2.0 AMP OPTIONAL FT600HA1BK



17.00 19.00 1.75 P 📼 CIRCUIT-OPTIONAL LIGHTED SWITCH

FT300HA1BK

Note: All cad drawings are shown with optional lighted switch. All units are also available without switch - see chart below.

Without Switch	With Lighted	Running						Rear Bracket Depth	
Part No.	Switch Part No.	CFM	Amps	Watts	Panel Width	Case Width	Case Depth	Min.	Max.
FT300TA1BK	FT300HA1BK	300	0.55	45	19	17.00	7.50	n/a	n/a
FT600TA1BK	FT600HA1BK	600	1.10	90	19	17.00	13.00	2.40	19.20
FT900TA1BK	FT900HA1BK	900	1.70	140	19	17.00	18.50	7.90	24.70

Technical references and CAD downloads available at www.hammondmfg.com

All dimensions in inches unless specified otherwise